IMAGE-TEK'S *APPLYPRO™ OEM*

All Electric, Modular Print Engine based Printer Applicator

PCM Image-Tek

APPLYPRO™ OEM

IMAGE-TEK'S APPLYPRO™ OEM

Printer Applicator Specifications

Image-Tek Performance Integrated with Intermec Technology

High Speed Labeling

The Apply Pro™ incorporates the versatility of modular bolt-on print engine technology and is designed for high-speed tamp-on labeling. The ApplyPro™ OEM has an optional RFID module and prints and applies labels at speeds up to one label every 1.5 seconds at a 14.0" stroke. Label placement accuracy makes it the ideal choice for RFID or barcode label applications. Label sizes range from 1.0" x 2.0" (25.4 mm x 50.8 mm) up to 6.69" x 8.0" (170 mm x 203.2 mm).

Flexible & Reliable

Avoid the cost of installing pneumatic lines with the all-electric Apply Pro™ OEM! It features flexible, plug-n-play design with only the best components. Built for reliability and engineered to be on-line, all of the time. The up-front engineered design makes the ApplyPro™ OEM easy to service and maintain.

Options

"T" mounting stand and accessories
Low stock early warning
3-light monitoring tower
Dust cover enclosure
Product sensor
RFID

Standard Application Arm

Variable stroke up to 14.0" (356 mm) from edge of applicator.
Optional 24" (610 mm) or 30" (762 mm) variable stroke.

Printer Specifications

Intermec PX4i / PX6i
203/300 dots per inch resolution (8/11.8 dots per mm)

Print Speed:

PX4i	4 to 12 ips (110 – 300 mm/s)
PX61	4 to 9 ips (110 – 225 mm/s)

Print Width:

PX4i	4.40" (112 mm)
PX6i	6.50" (167 mm)

Print Length:

PX4i	8 inches
PX6i	8 inches

Media Dimensions

Maximum media roll diameter 14.0" (356 mm)
Maximum media supply roll length 2,000 feet (610 m)

Total thickness:	0.003" – 0.010" (0.07 mm – 0.25 mm)
Core diameter:	3.0" (76 mm)
Label Width Min:	1.0" (25.4 mm)
Label Width Max:	6.69" (170 mm)
Label Length Min:	2.0" (50.8 mm)
Label Length Max:	8.0" (23 mm)

Ribbons

Outside Diameter Max:	3.2" (81 mm)
Roll Length Max:	23,600" (600 m)

Recommended to be as wide as media

Programming Language

Intermec IPL
Fingerprint/Direct Protocol

Environment

Operating Temperature	50° – 104°F (10° – 40°C)
Storage Temperature	32° – 120°F (0° – 49°C)
Relative Humidity	10 – 90% (Non condensing)

Utility Requirements

100 – 120 VAC or 220 – 240 VAC
50/60 Hz
NO AIR REQUIRED

Fonts and Graphics

There are 21 resident bitmap fonts (including OCR A and B)
3 resident outline fonts
Supports user-defined fonts & graphics
Supports True Type fonts

Electronics

Dual 32-bit RISC and CISC microprocessors
1 MB standard DRAM
RAM upgradeable to 8 Mb or 16 Mb SIMM

Bar Code Symbologies

All popular symbologies including; Codabar, Code 11, Code 128, Code 39, Code 93, HIHC, Interleaved 2 of 5, Postnet, LI PC/FAN, JIS-ITF

RFID Standards Supported

UHF (Ultra High Frequency)
EPC Class 1, EPC Class 0/0+
EPC Class 1, Gen 2
Upgrade Capability to support new standards & protocols

Communications Interface

RS-232up to 115.2kb/s
USE 1.1
EasyLan Internal Ethernet 100/10 Base T

Weight

160 Lbs.

Intermec®
expect MORE™

Intermec is a registered trademark of Intermec Technologies Corporation

Corporate World Headquarters
6001 36th Avenue West
Everett, WA 98203-1264

As part of our continuous design improvements, certain features, dimensions or performance characteristics may change without notice.