

IMAGE-TEK'S *APPLYPRO™ PX4i / PX6i*

All Electric Printer Applicator



APPLYPRO™ PX4i / PX6i

IMAGE-TEK'S APPLYPRO™ PX4i / PX6i

Printer Applicator Specifications

Image-Tek Performance Integrated with Intermec Technology

High Speed Labeling

The Apply Pro™ PX4i/PX6i is designed for high-speed tamp-on labeling applications. It can print and apply labels at speeds up to one label every 1.5 seconds at a 14.0" stroke. The accuracy of the label placement makes it the ideal choice for labeling. Label sizes range from 4.0" x 2.0" (101.60 mm x 50.8 mm) up to 4.4" x 8.0" (111.76 mm x 203.2 mm).

Flexible & Reliable

The PX4i/PX6i all electric version of this world renowned trade name has many of the innovations of Image-Tek's ApplyPro™ series of printer applicators and more. It features flexible, plug-n-play design with only the best components. It is built for reliability and is engineered to be on-line, all of the time. The up-front engineered design makes the ApplyPro™ PX4i/PX6i easy to service and maintain.

Options

- "T" mounting stand and accessories
- Low stock early warning
- 3-light monitoring tower
- Dust cover enclosure
- Product sensor
- RFID

Standard Application Arm

- Variable stroke up to 14.0" (356 mm) from edge of applicator
- Optional 30" (762 mm) variable stroke

Printer Specifications

Intermec PX4i / PX6i
203/300 dots per inch resolution
(8/11.8 dots per mm)

Print Speed:
PX4i 4 to 12 ips (110 – 300 mm/s)
PX6i 4 to 9 ips (110 – 225 mm/s)

Print Width:
PX4i 4.40" (112 mm)
PX6i 6.50" (167 mm)

Print Length:
PX4i 8 inches
PX6i 8 inches

Media Dimensions

Maximum media roll diameter
14.0" (356 mm) maximum

Media supply roll length
1,500 feet (500 m)

Total thickness:
0.003" – 0.010"
(0.07 mm – 0.25 mm)

Core diameter: 3.0" (76 mm)

Label Width Min: 2.0" (50.8 mm)

Label Width Max: 4.0" (114 mm)

Label Length Min: 1.0" (25.4 mm)

Label Length Max: 8.0" (23 mm)

Ribbons

Outside Diameter Max: 3.2" (81 mm)

Roll Length Max: 18,000" (457 m)

Recommended to be as wide as media

Programming Language

Intermec 1PL
Fingerprint/Direct Protocol

Environment

Operating Temperature 50° – 104°F
(10° – 40°C)

Storage Temperature 32° – 120°F
(0° – 70°C)

Relative Humidity 10 – 90%
(Non condensing)

Utility Requirements

100 – 120 VAC or 220 – 240 VAC
50/60 Hz
NO AIR REQUIRED

Fonts and Graphics

There are 21 resident bitmap fonts
(including OCR A and B)

3 resident outline fonts

Supports user-defined fonts & graphics

Supports True Type fonts

Electronics

Dual 32-bit RISC and CISC
microprocessors

1 MB standard DRAM

RAM upgradeable to 8 Mb or 16 Mb
SIMM

Bar Code Symbolologies

All popular symbolologies including;
Codabar, Code 11, Code 128, Code 39,
Code 93, HIHC, Interleaved 2 of 5,
Postnet, LI PC/FAN, JIS-ITF

Weight

112 Lbs. (includes cover @ 7 - 8 Lbs.)

Intermec®
e x p e c t **MORE™**

*Intermec is a registered trademark of
Intermec Technologies Corporation*

Corporate World Headquarters

6001 36th Avenue West
Everett, WA 98203-1264