

## DuraTHERM® Lightning IR Labels

Sensitivity Number: 450★

Adhesive: Permanent

Part Number	Label (Width) (Height) inches	Length (Feed) (Length) inches	Labels Per Roll	Rolls Per Carton	P R I N T E R S													
					301/E4	501	601	3000	3100	3240	3400/3400e/3440	3600	4000/4100	4420/4440	4400	4630	4830	7421/7422/C4
☉E06832	4.10	1.20	4528	4	•	•			•	•	•	•	•	•	•	•		+
☉E06265(s)	4.10	1.20	4528	4	•	•			•	•	•	•	•	•	•	•		+
E01919	4.00	6.50	905	4	•	•			•	•	•	•	•	•	•	•		+
E01918	4.00	6.00	979	4	•	•			•	•	•	•	•	•	•	•		+
E01915	3.15	5.00	1170	4	•	•			•	•	•	•	•	•	•	•		+
E01914	3.00	1.00	5333	4	•	•			•	•	•	•	•	•	•	•		+
E06132▲	2.50	1.00	5333	4	•			•	•	•	•	•	•	•	•	•		+
E01913	2.40	4.00	1454	8	•			•	•	•	•	•	•	•	•	•		+

(s) liner slit

☉ Sunquest Label Design

**Perfs:** Labels over 1.5 inches in length and 2.5 inches in width are perfed between labels unless noted by ▲.

★ **Sensitivity numbers:** Sensitivity numbers are material dependent and will be specified on each roll.

- On F2 and F4, media compatible with both half door and full door configurations.
- + Compatible with half door configuration only.

## DuraTHERM® Lightning IR Tag

Sensitivity Number: 480★

Part Number	Label (Width) (Height) inches	Length (Feed) (Length) inches	Labels Per Roll	Rolls Per Carton	P R I N T E R S													
					301/E4	501	601	3000	3100	3240	3400/3400e/3440	3600	4000/4100	4420/4440	4400	4630	4830	7421/7422/C4
045731	3.25	7.375	810	4					•	•	•	•	•	•	•	•		+

**Perfs:** Labels over 1.5 inches in length and 2.5 inches in width are perfed between labels unless noted by ▲.

★ **Sensitivity numbers:** Sensitivity numbers are material dependent and will be specified on each roll.

- On F2 and F4, media compatible with both half door and full door configurations.
- + Compatible with half door configuration only.